
















Specifications

LED Type	SMD 3528	Dimmable	Yes (compatible with BV311 RF dimmer & BV Dimmer)
LED Q'ty/m	60pcs	IP grade	IP22 (IP65 & IP67&IP68 available upon request)
Input Voltage	12V / 24VDC Constant Voltage	Installation	3M™ double sided tape
Power	4.8W	Working Temperature	-25~+60 °C
Cutting length	12V 50mm 3 LEDs 24V 100mm 6 LEDs	Max run	12V 5 meters 24V 10 meters
Strip Width	8mm	Certification	E354137 cULus Listed, CE, RoHs
Viewing Angle	120°	Warranty	5 years/ 3 years [Ⓞ]

Order Code	CCT/ Color	CRI	Lumen/M ^②
FN-3528A-60-12-25K	 2425-2580K	80+, 90+, 95+	312
FN-3528A-60-12-27K	 2645-2800K	80+, 90+, 95+	312
FN-3528A-60-12-30K	 2850-3025K	80+, 90+, 95+	336
FN-3528A-60-12-35K	 3270-3545K	80+, 90+, 95+	336
FN-3528A-60-12-42K	 3840-4060K	80+, 90+, 95+	384
FN-3528A-60-12-50K	 4830-5095K	80+, 90+, 95+	384
FN-3528A-60-12-55K	 5400-5800K	80+, 90+, 95+	288
FN-3528A-60-12-65K	 6260-6680K	80+, 90+, 95+	360
FN-3528A-60-12-90K	 7836-9000K	80+	312
FN-3528A-60-12-R	 625nm	-	156
FN-3528A-60-12-G	 525nm	-	255
FN-3528A-60-12-B	 465nm	-	99
FN-3528A-60-12-Y	 592nm	-	120
FN-3528A-30-12-PK	 Pink	-	210
FN-3528A-30-12-PL	 Purple	-	18

Note[Ⓞ]: Contact Blueview for exact warranty period and policy

Note^②: Lumen output are based on CRI80+ measured according to PMS-80, with a tolerance of +/- 5%

Note[Ⓞ]: Standard package: 5m/roll

BLUEVIEW ELEC-OPTIC TECH CO.,LTD

Tel: +86-28-8148 0011 Fax: +86-28-8148 1258
 Mail: sales@blueviewled.com Web.: www.blueviewled.com
 Add: No.1000, Section 2, 2nd Konggang Road, Southwest
 Aviation Industrial Development Zone, Chengdu, Sichuan, China.
 Zip code: 610207

Specifications are subject to change without notice.
 ©Blueview™ 2016 – All rights reserved. Made in China.

